



SAFETY DATA SHEET

according to Regulation (EU) 2015/830

Page 1/4

BROAD SPECTRUM ODOUR NEUTRALISER

Revision 1

Revision date 02/04/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	BROAD SPECTRUM ODOUR NEUTRALISER
--------------	----------------------------------

1.3. Details of the supplier of the safety data sheet

Company	Astral CSL
Address	Unit 36, Greenfield business park, Bagillt Road Greenfield Holywell Clwyd
Web	CH8 7HJ
Telephone	0161 643 0260
EMAIL	SALES@ASTRALCSL.COM
I	
Email address of the competent person	r.murie@astralcsl.com

1.4. Emergency telephone number

Emergency telephone number	0044 (0) 7725 123 546
Company	Roger Murie

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

2.1.1. Classification - 1999/45/E C	Xi; R43 Symbols: Xi: Irritant.
Main hazards	May cause sensitisation by skin contact.
2.1.2. Classification - EC 1272/2008	Skin Irrit. 2: H315; Eye Irrit. 2: H319;

2.2. Label elements

Hazard pictograms	
Signal Word	Warning
Hazard Statement	Skin Irrit. 2: H315 - Causes skin irritation. Eye Irrit. 2: H319 - Causes serious eye irritation.
Precautionary Statement: Prevention	P264 - Wash thoroughly after handling. P280 - Wear protective gloves/protective clothing/eye protection/face protection.
Precautionary Statement: Response	P302+P352 - IF ON SKIN: Wash with plenty of water/ . P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P321 - Specific treatment (see on this label).

BROAD SPECTRUM ODOUR
NEUTRALISER

Revision 1

Revision date 02/04/2024

2.2. Label elements

P332+P313 - If skin irritation occurs: Get medical advice/attention.
P337+P313 - If eye irritation persists: Get medical advice/attention.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

67/548/EEC / 1999/45/EC

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		0.5 - 1%	F; R11 Xi; R36 R67	
SALICAT MM					0.5 - 1%	C; R34 Xi; R43 R52/53	

EC 1272/2008

Chemical Name	Index No.	CAS No.	EC No.	REACH Registration Number	Conc. (%w/w)	Classification	M-factor.
Isopropanol (Propan-2-ol)	603-117-00-0	67-63-0	200-661-7		0.5 - 1%	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336;	
SALICAT MM					0.5 - 1%	Skin Corr. 1A: H314;	

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation	If you feel unwell, seek medical advice (show the label where possible).
Eye contact	Avoid contact with eyes. Bathe the eye with running water for 15 minutes. Contact lenses should be removed. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Irritating to eyes.
Skin contact	Avoid contact with eyes and skin. Avoid contact with skin. If you feel unwell, seek medical advice (show the label where possible). Irritant, defatting, skin. Rinse immediately with plenty of water.
Ingestion	If swallowed, rinse mouth with water (only if the person is conscious). If you feel unwell, seek medical advice (show the label where possible). Seek medical attention if irritation or symptoms persist.

4.2. Most important symptoms and effects, both acute and delayed

Eye contact	Avoid contact with eyes and skin. Bathe the eye with running water for 15 minutes. If you feel unwell, seek medical advice (show the label where possible). In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
-------------	---

SECTION 5: Firefighting measures

5.2. Special hazards arising from the substance or mixture

	No Significant Hazard.
--	------------------------

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

	Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with skin and eyes.
--	---

6.3. Methods and material for containment and cleaning up

	Absorb with inert, absorbent material. Clean spillage area thoroughly with plenty of water.
--	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

	Adopt best Manual Handling considerations when handling, carrying and dispensing. Avoid contact with eyes and skin. Wear suitable protective clothing and eye/face protection.
--	--

7.2. Conditions for safe storage, including any incompatibilities

	Keep locked up and out of the reach of children. Keep only in the original container.
--	---

BROAD SPECTRUM ODOUR NEAUTRALISER

Revision 1

Revision date 02/04/2024

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Isopropanol (Propan-2-ol)

WEL 8-hr limit ppm: 400	WEL 8-hr limit mg/m3: 999
WEL 15 min limit ppm: 500	WEL 15 min limit mg/m3: 1250
WEL 8-hr limit mg/m3 total - inhalable dust:	WEL 15 min limit mg/m3 total - inhalable dust:
WEL 8-hr limit mg/m3 total - respirable dust:	WEL 15 min limit mg/m3 total - respirable dust:

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Liquid
Colour	Cloudy
Odour	Characteristic

SECTION 10: Stability and reactivity

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No Significant Hazard.

SECTION 11: Toxicological information

11.1.4. Toxicological Information

No data available

SECTION 12: Ecological information

12.1. Toxicity

No data available

SECTION 13: Disposal considerations

Disposal methods

For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.

SECTION 14: Transport information

SECTION 15: Regulatory information

SECTION 16: Other information

Other information

Text of risk phrases in Section 3

R11 - Highly flammable.
R34 - Causes burns.
R36 - Irritating to eyes.
R43 - May cause sensitisation by skin contact.
R52/53 - Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

BROAD SPECTRUM ODOUR NEAUTRALISER

Revision 1

Revision date 02/04/2024

Other information

Text of Hazard Statements in Section 3	environment.
	R67 - Vapours may cause drowsiness and dizziness.
	Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
	Eye Irrit. 2: H319 - Causes serious eye irritation.
	STOT SE 3: H336 - May cause drowsiness or dizziness.
	Skin Corr. 1A: H314 - Causes severe skin burns and eye damage.